

ON-563

Power by WEICHAI

6M33D633E200

Prime power: 450KW/562.5KVA

Standby power: 500KW/625KVA

GENERATING POWER SOLUTIONS

Increased availability for new operations

Reliable, robust and versatile generator.
Ready to deliver power for a next job.

Increased uptime during operations

Once installed on the end-user-site, the generator will be ready to run: "peace of mind" operation.

Reduced transport and installation costs



The compact and robust design with integrated transport features enables faster and safer transport and installation.

Reduced service & maintenance costs

Longer service intervals.
Quicker and more efficient service jobs.

Premium resale value

Designed and built to last.



DIMENSION		OPEN TYPE		SILENT TYPE
	Length (L)	mm	3550	5482
	Width (W)	mm	1602	1830
	Height (H)	mm	2205	2500
	Dry weight	kg	4328	6286
	Fuel tank	L	NA	740

ONEWPOWER

WWW.ONEWPOWER.COM

Technical Data

Model ON-563

Rated prime power	KW	450
Rated standard power	KW	500
Rated voltage line to line	V	380~415
Maximun sound level	dB(@7m)	≤ 72

Engine

Model	6M33D633E200
Aspiration	Turbochargine and aftercooled
Fuel system	mechanical pump
No. cylinders	6
Displacement	Liquid 19.6
Bore*Stroke	mm 150*185
Compression ratio	15:1
Rated speed	r/min 1500
Rated net power(with fan)	Kw 450
Governor type	Electronic

Exhaust system

Exhaust gas flow	3255.7kg/h
Exhaust gas temp	° F (° C) < 750
Max back pressure	7.5Kpa

Aspiration system

Max inlet pressure	kPa ≤ 3.5
Combustion volume	L/s /
Air flow	kg/h 2933

Fuel system

100% load(Prime power)	L/h 137
75% load(Prime power)	L/h 100
50% load(Prime power)	L/h 67.6
Fuel tank capacity	L 740

Lubrication system

Oil capacity	L 61
Oil consumption	L/H 137
Oil pressure	kPa 10
(continuous operation)	

Cooling system

Coolant capacity	L 43.93
Thermostat operation range	°C 76-88
Max water temperature	°C 98

Alternator

Model	ON-563
Phase	3
Voltage	V 380~415
Bearing	1
Power factor	0.8
Frequency	Hz 50
Prime power	KW 450
Exciter Type	Brushless, self-excitation
Voltage regulation	% ±0.5
Protection Grade	IP 23
Insulation grade	H/H
Altitude	m ≤1000

Controller

Model	
Protective functions:	
■ Low oil pressure	
■ High water temperature	
■ High/low voltage	
■ High Engine Temperature and Overspeed.	
■ Voltage regulator frequency regulator	
■ Emergency stop	
■ Start failure	



Control Module Options



- Auto generator control module
- Control module with "Three Remote Control" functions
- ATS auto load transfer screen
- Synchronising control modules
- Power output cabinet

Standard features

- Engine
- Radiator 50°C max, fans are driven by belt
- 24V charge alternator
- Alternator: single bearing alternator IP23, insulation class H/H
- Standard auto control system
- One set of air filter, fuel filter, oil filter
- Main line circuit breaker/MCCB
- Base fuel tank
- Two 24V batteries, rac and cable
- Exhaust system(Ripple flex exhaust pipe, exhaust siphon, flange, muffler)
- User manual

Options

- Battery charge
 - Engine heater
 - Alternator heater
 - PMG
 - Water oil separator
 - Daily fuel tank
 - Remote control panel
 - Automatic transfer switch/ATS
 - Switch box
- Standard: ● Options: ○

Warranty



WEICHAH ENGINE

12 months from date of purchase and 1000 hours.

Generator

12 months from date of purchase or 1000 hours (whichever occurs first).

Dimensions



ONEWPOWER

ADD: NO . 1 0 7 XIYUAN ROAD , JINAN DISTRICT,
FUZHOU CITY, FUJIAN, CHINA
Phone: 15980204507 E-mail: jina@onewpower.com
WWW.ONEWPOWER.COM

